


# ShieldECO ANTI-GLARE

The ShieldECO range now offers an anti-glare version, without sacrificing any of the features of the popular fitting. It has all the features required of an everyday downlight; fire rated, IP65 and dimmable. Tool-less and quick to install due to the 4 way push fit, screwless terminal block. Cool white and Warm white.



NEW  
PRODUCT

FIRE  
RATED

IP65  
RATED

DIMMABLE

FAST  
FIX

5  
Year  
Warranty

SMD


IP65

80  
CRI

60°

A

- Constructed from steel and acrylic
- 4W LED module (SMD)
- Min. void: 100mm
- Compatible dimmer 75021 (150W), see page 300



Can be covered with insulation

| CODE  | DESCRIPTION             | FINISH     | K    | LM  | LM/W | DIMENSIONS                  | CUT OUT   |
|-------|-------------------------|------------|------|-----|------|-----------------------------|-----------|
| 81016 | ShieldECO Anti-glare 4W | Matt white | 3000 | 500 | 125  | Proj: 3mm H: 80mm Dia: 90mm | Dia: 80mm |
| 81017 | ShieldECO Anti-glare 4W | Matt white | 4000 | 500 | 125  | Proj: 3mm H: 80mm Dia: 90mm | Dia: 80mm |

# ShieldPRO

The ShieldPRO is Saxby's new signature downlight. This fitting comes with a 2-way "Plug and Play" DC connector which allows users to loop in and out. The DC connector allows for easy removal of the fitting during wiring, painting and decorating. The DC connector has a simple 3-way switch which allows users to choose between 3000K, 4200K or 6000K. Other features include: the option to be covered with insulation, fits into shallow ceiling voids, IP65-rated, and fully fire-rated for 30, 60 and 90-minute ceilings. The ShieldPRO has two bezel colour options, Satin nickel and Chrome, and these can be easily removed or added by twisting on and off.



NEW  
PRODUCT

CCT  
3000K / 4200K / 6000K

FIRE  
RATED

IP65  
RATED

DIMMABLE

5  
Year  
Warranty

SMD

IP65

80  
CRI

60°

A

- Matt white finish (Matt white bezel included)
- 7W LED module (SMD)
- Interchangeable bezel option - Satin nickel (90377) & Polished chrome (90378)
- Min. void 50mm
- Compatible dimmer 75021 (150W), see page 300



Detachable connector



Fast-fix connector



50mm - Low profile



Insulation covered

| CODE  | DESCRIPTION  | FINISH       | K                  | LM  | LM/W | DIMENSIONS                  | CUT OUT   |
|-------|--------------|--------------|--------------------|-----|------|-----------------------------|-----------|
| 90376 | ShieldPRO 7W | Matt white   | 3000 / 4200 / 6000 | 800 | 114  | Proj: 3mm H: 50mm Dia: 88mm | Dia: 70mm |
| 90377 | Bezel        | Satin nickel |                    |     |      |                             |           |
| 90378 | Bezel        | Chrome       |                    |     |      |                             |           |