essentials™

Product Code: CL660B

Technical Specification

Luckinslive 407530678

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch







Insert: Urea

Terminal Torque Value (Nm) 1.2

GridPro Module: GM2018PW

Frequency (Hz) 50

General Information

 $\textbf{Dimensions (mm)} \quad 80 \ (\text{W}) \times 80 \ (\text{H}) \times 42 \ (\text{D})$

Plate Fixing Centres - Horizontal (mm) 60.3

Style Metal Clad

Colour Grey

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel
Earth Plate & Yoke: Mild Steel
Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

citilitat serews. Steet & Tettow Lassivated

Operating Voltage (AC) 250

Resistive Load Rating (A) 20 Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Modular Rocker Switches Yes

Double Pole Switch Yes

Twin Earth Terminals Yes

Product Marking On & Off

Supplied Back Box Depth (mm) 40

Back Box Knockouts - Total (mm) None

Back Box Earth Terminal Supplied Yes

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.











Specification is subject to change without notice. Errors & Omissions excluded.