


Technical Specification



Product Code: VPCH655WH







General Information

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian

Finish Polished Chrome

Insert Colour White Gasket Colour White

> Materials Front Plate: Stainless Steel Insert: Urea

> > Earth Plate & Yoke: Mild Steel Neon Lens: Polycarbonate

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass GridPro Module: GM2018PW

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13 Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Modular Rocker Switches Yes Double Pole Switch Twin Earth Terminals Yes Neon Indicator

Indicator Colour

Product Marking On & Off Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

> Warranty (Years) 20

Standards BS EN 60669-1, BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com