

Surface & Suspended



Slim depth of just 38mm



UGR19 for low glare




75% down / 25% up ratio
uses light efficiently to
reduces the amount of
luminaires required

Guarantee	7 years (product), 5 years (emerg battery)
Wattage	45W
IP rating	IP20
IK rating	IK02
Dimmable	Yes (DALI-2, PUSH-DIM)
Input	220-240V 50/60Hz
LED lifetime	54,000h L80
Emergency version available	Yes, Self-Test
Install connector type	Push-fit terminal, loop-in/loop-out
Ambient temperature	0°C to 40°C
Electric class	1




Versa Tile Silver

UGR19 architectural linear suitable for surface, suspension or wall mount



Connector kit
VTSCON*



Wall mount kit
VTSWALL*

*By custom request, please contact our sales team on 01604 495151

Product code	Finish	Type	W	Colour	Beam	lm	lm/W
VTSID	Silver	DALI-2 dimmable	45W	4000K	80	5000	110
VTSIDEM	Silver	Emergency DALI-2 dimmable	45W	4000K	80	5000	110
VTSIDP	Silver	DALI-2 Dimmable PIR Sensor	45W	4000K	80	5000	110
VTSIDPEM	Silver	Emergency DALI-2 Dimmable PIR Sensor	45W	4000K	80	5000	110
VTSIN	Silver	Standard	45W	4000K	80	5000	110
VTSINEM	Silver	Emergency	45W	4000K	80	5000	110
VTSINP	Silver	PIR sensor	45W	4000K	80	5000	110
VTSINPEM	Silver	Emergency	45W	4000K	80	5000	110

