

WEATHERGUARD SITE A-FRAME

PORTABLE SITE LIGHTING

Our Plasterer's A-Frame is a handy addition to the Weatherguard Site range. This portable fitting is easy to relocate and features a useful cable storage facility



Features

- Lightweight and easy to relocate on site
- Strong, stable frame
- Includes 2x110V power outlets for connecting more fittings or power tools
- Supplied with 5m cable and pre-wired plug



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS220Y/AF	Weatherguard Site A-Frame	2000 lm		20W	100 lm/W

Product Information

Guarantee	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate, Steel Frame & Polypropylene Socket
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Yellow
LED Life Expectancy	L80B50 30,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C



WEATHERGUARD SITE A-FRAME

PORTABLE SITE LIGHTING

Packaging Information

Dimensions (mm)	L: 880 x W: 305 mm
Product Net Weight (kg)	3 kg
Barcode	5055807622769
Box Dimensions (mm)	L: 775 x W: 230 x D: 165mm

Box Gross Weight (kg)	3.45 kg
Outer Carton Dimensions (mm)	L: 755 x W: 230 x D: 160mm

