

# WEATHERGUARD SITE TRIPOD HEAD

## WEATHERGUARD SITE TRIPOD HEAD 600MM

Weatherguard Site tripod mounted fittings offer ultimate flexibility on site. The heads are supplied ready to mount onto the tripod, complete with 2x110V power outlets and 5m of cable.



### Features

- Fitted with twin 110V sockets
- Pre-wired with 5m cable and plug
- Unique, future proof replaceable LED module



### Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS220Y/TH	Weatherguard Site Tripod Head 600mm	2000lm		20W	100 lm/W

### Product Information

Guarantee	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Finish	Yellow

LED Life Expectancy	L80B50 30,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C

# WEATHERGUARD SITE TRIPOD HEAD

## WEATHERGUARD SITE TRIPOD HEAD 600MM

### Packaging Information

Dimensions (mm)	L: 664 x W: 103 x D: 78 mm
Product Net Weight (kg)	2.73 kg
Barcode	5055807623674

Box Dimensions (mm)	L: 690 x W: 195 x D: 110 mm
Box Gross Weight (kg)	3.1 kg

