

VENUS

COMPACT DOWNLIGHTS

Venus is a new range of compact commercial downlights, designed as the perfect retrofit solution to compact fluorescent installations. The die-cast aluminium range features adjustable fixing brackets and optional floating glass attachments.



Features

- High quality, die-cast aluminium construction
- 1000, 2000, 3000 lumen output options
- 150, 170 & 200mm cut outs, ideal for PL downlight retrofit
- Optional floating glass attachment
- Ceiling brackets adjust from below

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
VEN200/3-40	Venus Downlight 200mm 3200lm 4000K	3200 lm		29W	110 lm/W

Product Information

Guarantee	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	4000K
IP Rating	IP54 (from below ceiling)
Voltage	230V
Material (Body/Housing)	Die-Cast Aluminium
Material (Diffuser/Cover)	PMMA
Colour Rendition (CRI)	Ra > 80

Colour Finish	White RAL9003
LED Life Expectancy	L80B50 50,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class II
Working Temperature	-20°C to 40°C

VENUS

COMPACT DOWNLIGHTS

Packaging Information

Dimensions (mm)	Ø: 230 x D: 86 mm
Product Net Weight (kg)	1.3 kg
Barcode	5055807623490
Box Dimensions (mm)	L: 280 x W: 235 x D: 115 mm
Box Gross Weight (kg)	1.45 kg

Units/Outer Carton	8
Outer Carton Barcode	15055807623497
Outer Carton Dimensions (mm)	L: 580 x W: 490 x D: 245 mm
Outer Carton Gross Weight (kg)	12.6 kg

