

Product Code: SFBK652BK

Technical Specification

Luckinslive 435277822

Description: 13A Double Pole Switched Fused Connection Unit With Neon







General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Matt Black

Insert Colour Black

Compatible Cover Plate SCP252#

Materials Cover Plate: Polycarbonate Insert: Polycarbonate

Rear Housing: Urea Rear Housing: Urea Neon Lens: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel

Internal Busbars: Formed Pressed Brass

Frequency (Hz) 50

Anti Microbial Certified Operating Voltage (AC) 250

Resistive Load Rating (A) 13

> Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Twin Earth Terminals

> Neon Indicator Yes Indicator Colour Red

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal









