



DATASHEET



BATSCWST5

230V 5ft 22/41W CCT Adjustable Self-Test
Emergency Batten

www.mlaccessories.co.uk



| MLA PART CODE | BATSCWST5 |
|-------------------------------|--|
| DESCRIPTION | 230V 5ft 22/41W CCT Adjustable Self-Test Emergency Batten |
| NET WEIGHT (KG) | 1.86 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1525 Width - 61 Projection - 71 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 22/41 |
| LAMP TECHNOLOGY | LED |
| LUMENS (LM) | 2970/3300/3210, 5170/6040/5630 |
| LUMENS LIGHT SOURCE ONLY (LM) | 6520 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 160.58 |
| LUMENS EMERGENCY MODE (LM) | 360 |
| CIRCUIT WATTAGE (W) | 40.64 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.18 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0 |
| PST-LM | 0 |
| BEAM ANGLE (DEGREES) | 145 |
| L70B50 LIFESPAN (HRS) | 60,000 |

| | |
|--|--|
| DIMMABLE | No |
| EMERGENCY | Maintained / Non-maintained / Switched |
| SELF-TEST | Yes |
| OPERATING TEMPERATURE | -5~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 21/42W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 480/960mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 96.9 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C |
| BATTERY INCLUDED | Yes |
| WARRANTY | 5year(s) |
| WARRANTY INFORMATION | (excluding battery) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270881479 |

Date Created: 08/01/2024 20:54

