

Technical Specification



Product Code: MD023PN-BL Description: 20A Double Pole Switch With Neon Module





General Information

 $\label{eq:definition} \textbf{Dimensions} \qquad 41 \text{mm (W)} \ \text{x} \ 52.5 \text{mm (H)} \ \text{x} \ 22 \text{mm (D)}$

Aperture Dimensions 32mm (W) x 31.5mm (H)

Finish Pearl Nickel

Materials Rocker Switch: Urea

Rear Housing: Nylon Switch Cover: Stainless Steel

Neon Cover: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V 50Hz
Load Rating 20A
Terminal Size 4.4mmø
Terminal Torque 1.2Nm

Terminal Capacity 4 x 1.5mm² or 2 x 2.5mm²

Neon Indicator Yes (Red)
Product Markings Boiler

Back Box Depth Dependent On Plate Used

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.