

## **Technical Specification**

Product Code: GM2018BKAB-FD Description: 20AX Double Pole Switch Module





## **General Information**

**Dimensions** 24.5mm (W) x 50mm (H) x 22.5mm (D)

Aperture Dimensions 20mm (W) x 35mm (H)

Module Frame Finish Black

Switch Finish Antique Brass

**Laser Etched Legend** Fridge

Materials Body & Insert: Nylon

Switch: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Maximum Voltage 250V 50Hz

Load Rating 20AX (Suitable For Inductive Loads)

Terminal Size 5mmø
Termination Type Screw
Terminal Torque 1.2Nm

**Terminal Capacity** 3 x 2.5mm<sup>2</sup> or 1 x 4mm<sup>2</sup>

Product Markings Fridge

Back Box Depth Dependent On Plate Used

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621

