

Technical Specification

Product Code: SFBK204BK

Luckinslive 435276043



Description: 50A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet





General Information

Insert Dimensions (mm) Plate Dimensions (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Insert Colour	142.5 (W) x 82.5 (H) x 2.5 (D) 146 (W) x 86 (H) x 4 (D) 120.6 Screwless Complete Matt Black Black	
Compatible Cover Plate	SCP204#	
Materials	Cover Plate: Polycarbonate Switch & Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Insert: Polycarbonate Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	50	
Termination Type	Screw	
Terminal Size (mm)	Ø6 Termina	al Torque Value (Nm) 2.5
Terminal Capacity - Solid (mm ²)	1 × 16	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	Cooker	
Minimum Back Box Depth (mm)	47	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	
Standards BS 4177		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









