

**HE7230 • HE7245 • HE7260****Wireless controlled recessed ceiling fan heaters**

Recessed ceiling heaters are designed for discreet positioning in a suspended 600mm standard ceiling panel. They are ideal to heat areas such as shops and offices.



- Compatible with run-back timers and advanced single-zone controllers.
- Run-back time controllers are compatible with SL heaters only.
- Fits standard 600mm modular suspended ceiling system.
- Sealed heater box for improved energy efficiency.
- Will fit shallow 210mm recess.
- Light weight for easy installation.
- Quiet operation.
- Automatic safety cut-out.
- Fan only setting for air circulation (for RX models).
- Wider operating range (for RX models).
- LED indicator light.
- Complete with white aluminium diffuser.

Model No.	kW	Depth x Width x Length (mm)	Weight (kg)	Optimum Ceiling Height (m)	dBA
HE7230SL	3	175 x 595 x 595	7.5	3.0	37
HE7230RX	3	175 x 595 x 595	7.5	3.0	37
HE7245SL	4.5	175 x 595 x 595	7.5	3.3	38
HE7245RX	4.5	175 x 595 x 595	7.5	3.3	38
HE7260SL	6	175 x 595 x 595	10.5	3.6	40
HE7260RX	6	175 x 595 x 595	10.5	3.6	40

Note: Wireless controllers to be purchased separately.

## CHOICE OF WIRELESS CONTROLLERS



### RUN-BACK TIME CONTROL & THERMOSTAT

Building owners or operators have a variety of SL heating control options through SLPB, SLVT, SLVTB, SLPBWP or SLPBWP wireless controllers connected to one or multiple SL heaters. Refer to page 33 for details.



### ADVANCED SINGLE ZONE CONTROLLERS

The CRXSL, SLTI and LC controllers are compatible with all RX and SL heater models and offer better energy saving features including an optional open window detection. Refer to page 36 for details.