

PHOTOCELLS

PHOTOCELL HEAD

Suitable for integration into luminaires or stand alone, our photocells all include a delay circuit to prevent nuisance switching.





Features

- Designed for use with LED loads
- All include a switching delay to prevent false switching due to headlights or cloud cover
- Provide automatic control dusk to dawn
- Deliver increased energy savings



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
PC10AH	Photocell Head			1000W	

Product Information

Warranty	1 Year
IP Rating	IP65

Material (Body/Housing)	Polycarbonate	
Approval	UKCA CE	

Tel: 0114 279 8999 | Email: sales@redarrowelectrical.co.uk | redarrowelectrical.co.uk



PHOTOCELLS

PHOTOCELL HEAD

Packaging Information

Dimensions (mm)	L: 64 x Ø: 80 mm	
Product Net Weight (kg)	0.11 kg	
Barcode	5055807609388	
Box Dimensions (mm)	L: 85 x W: 85 x D: 70 mm	
Box Gross Weight (kg)	0.12 kg	

Units/Outer Carton	100	
Outer Carton Dimensions (mm)	L: 430 x W: 430 x D: 320 mm	
Outer Carton Gross Weight (kg)	12.85 kg	

Tel: 0114 279 8999 | Email: sales@redarrowelectrical.co.uk | redarrowelectrical.co.uk