

Technical Specification



Fort			
1	2	3	
4	5	6	
7	8	9	
*	0	#	

General Information

deneral information			
Dimensions (mm)		135 x 90 x 15	
Fob Reader Operating Frequency (KHz)		125	
Fob Reader Operating Distance	<50		
PIN length		6 for Administration, 4 for User	
Backlight		Keys (Blue LED's)	
Tamper Facility		Yes	
Status Indication		Green LED	
Weight (Kg)		0.14	
Warranty (Years)		1	
Construction			
Materials	ABS		
Finish	White		
Mounting	Surface		
Programming			

Supply & Power				
Operating Voltage (V DC)	4.5			
Power Consumption (A)	0.06			
Power Reserve	12 Months (Approx.)			
Battery Type	AAA (LR03) x 3			
Transmission				
Transmission Frequency (M	2) 433			
Transmission Distance	n) 80 (open field)			
Environment				
Operating Temperature (°	C) -10 to 55			
Relative Humidity Resistance (9	<80 (non-condensing)			

Available Operations Home/Disarm/SOS

Supplied Fort Keypad, 3 x AAA Batteries, Mounting Screws & Wall plugs, User Guide

Additional Information Disarm, Home Mode and Panic Function (Arm Via Fob)

Features

Can be used for a Full Alarm, Home Alarm, Disarmed, or Active System into SOS Powered VIA 3 x AAA batteries Fob can be used to arm and disarm system Tamper facility built in

Accessories

ECSPPX: Smart Alarm Proximity Tag

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com

