

RHOMBUS PRO

HIGH EFFICACY TP(A) BACK-LIT PANEL

Delivering outstanding efficacy and in a wide range of options, Rhombus Pro offers the perfect solution for any commercial application. All feature TP(a) diffusers and Philips drivers as standard.



Features

- Excellent efficacy - up to 140 lm/W
- TP(a) diffusers as standard
- Lumen output range 3000-5600 lm
- Extensive range - 600 x 600mm, 600 x 1200mm & 300 x 1200mm
- Emergency options & surface mount kits available

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
RBP12644-30	Rhombus Pro 600mm x 1200mm High Output TP(a)	5720 lm		44W	130 lm/W

Product Information

Guarantee	7 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	3000K
IP Rating	IP40
IK Rating	IK03
Voltage	230V
Material (Body/Housing)	Steel & Aluminium
Material (Diffuser/Cover)	TP(a) Rated Styrene
Colour Rendition (CRI)	Ra > 80

Colour Finish	White RAL9003
LED Life Expectancy	L80B50 50,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	-20°C to 45°C



RHOMBUS PRO

HIGH EFFICACY TP(A) BACK-LIT PANEL

Packaging Information

Dimensions (mm)	L: 1195 x W: 595 x D: 32 mm
Product Net Weight (kg)	3.45 kg
Barcode	5055807623063
Box Dimensions (mm)	L: 1275 x W: 615 x D: 42 mm
Box Gross Weight (kg)	4 kg

Units/Outer Carton	4
Outer Carton Barcode	15055807623060
Outer Carton Dimensions (mm)	L: 1290 x W: 630 x D: 185 mm
Outer Carton Gross Weight (kg)	17.5 kg

