essentials™

Product Code: WA072

Technical Specification

Luckinslive 389120339

Description: 30A Junction Box Selective Entry 3 Terminal





General Information

Dimensions (mm) 90 (Dia) x 35

Colour White

Materials Body: Urea

Terminal Screws: Steel and Yellow

Passivated

Anti Microbial Certified Yes

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 30
Number Of Terminals 3
Termination Type Screw

Terminal Size (mm) 4.6×11.5 Terminal Capacity - Solid (mm²) 2×4

Entry Knockout Dimensions (mm) 16 x 8 (16 x 16 Full) (x4)

Ingress Protection IP20

Operational Temperature (°C) -20 to +55

Warranty (Years) 10

Standards BS EN 60670-1, BS EN 60670-22

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Specification is subject to change without notice. Errors & Omissions excluded.







Earth Terminals: Brass

Terminal Torque Value (Nm) 0.8

