

Technical Specification

Luckinslive 435284307







Insert & Housing: Urea

Earth Strap: Mild Steel

Indicator Colour

Neon Lens: Polycarbonate

Frequency (Hz) 50

Terminal Screws: Steel & Yellow Passivated

General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Finish Matt Black

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Fuse Drawer Cover: Stainless Steel

Terminals: Brass

Internal Busbars: Formed Pressed Brass

Anti Microbial Certified Operating Voltage (AC) 250

Resistive Load Rating (A) 13

> Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched

Twin Earth Terminals

Neon Indicator

Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362


Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Supplied with Matt Black plate fixing screws.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal













Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

Specification is subject to change without notice. Errors & Omissions excluded.