

Technical Specification

Product Code: GM2018NBKSB-WDR      Description: 20AX Double Pole Switch With Neon Module



General Information

|                         |   |
|-------------------------|---|
| Dimensions              | 24.5mm (W) x 50mm (H) x 22.5mm (D)  |
| Aperture Dimensions     | 20mm (W) x 35mm (H)   |
| Module Frame Finish     | Black   |
| Switch Finish           | Satin Brass   |
| Laser Etched Legend     | Warming Drawer  |
| Materials               | Body & Insert: Nylon<br>Switch: Urea<br>Neon Lens: Polycarbonate<br>Switch Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass |
| Maximum Voltage         | 250V 50Hz   |
| Load Rating             | 20AX (Suitable For Inductive Loads)   |
| Terminal Size           | 5mmø  |
| Termination Type        | Screw   |
| Terminal Torque         | 1.2Nm   |
| Terminal Capacity       | 3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup>   |
| Neon Indicator          | Yes (Red)   |
| Product Markings        | Warming Drawer  |
| Back Box Depth          | Dependent On Plate Used   |
| Operational Temperature | -5°C to +40°C   |
| Warranty                | 10 Years  |
| Standards               | BS EN 60669-1:2018  |

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621