6311

KO)

m20

ESSENTIALSTM

0

0

CL049

*

0

1





CL158





All New Media[™] plates are suitable for use with standard euro module inserts.



Selecting from a range of module inserts covering all manner of media transfer, the installer will now be able to configure their own arrangement of TV, radio or satellite reception, plus speaker, telephone and data outlets. All modules can be inserted into single or double wall plates, fitted

Telephone & Coaxial Socket Outlets

- CL120 Single Telephone Outlet Master CL158 Single Isolated Coaxial Outlet
 - Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated

Unfurnished Plates - New Media[™]

CL311 1 Gang New Media[™] Unfurnished Plate - 2 Apertures CL312 2 Gang New Media[™] Unfurnished Plate - 4 Apertures

Back Box Depth: 40mm Minimum, Knock-outs: 20mm Dimensions: 1 Gang: (80mm x 80mm), 2 Gang: (140mm x 80mm)

outlet is required.

CLICK



20A Control Switches with Optional Flex Outlet Fused Connection Units With Optional Flex Outlet

CL049

CL050

CL051

13A Fused Connection Unit

13A DP Switched Fused Connection Unit

Standards: BS EN 60669 20A, 13A & 3A: BS 1363, and BS 1362 (Fuse) Cable Size: 1 x 16mm² 13A & 3A: 3 x 2.5mm² or 2 x 4mm² 660: 3 x 2.5mm2, 2 x 4mm2 Knock-outs: 20mm Dimensions: 1 Gang: (80mm x 80mm), 2 Gang: (140mm x 80mm) Back Box Depth: 40mm 45A: 50mm

CL022 20A DP Switch

Lockable Switches

CL660B

45A Switches

CL023 20A DP Switch With Neon

(No Knockouts)